

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name	:	Neomax I (Neomat/Maxi I)
Product code	:	115825E
Use of the Substance/Mixture	:	Floor Cleaner
Substance type:	:	Mixture
		For professional users only.
Product dilution information	:	No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	:	Floor cleaner. Semi-Automatic process Floor cleaner. Manual process
Recommended restrictions on use	:	Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company	 Ecolab Ltd. PO Box 11; Winnington Avenue Northwich, Cheshire, United Kingdom CW8 4DX + 44 (0)1606 74488 ccs@ecolab.com
	ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number	:	Food & Beverage, Institutional, Agriculture, Textile Hygiene: Northwich: +44 (0)1606 74488 Healthcare Leeds: +44 (0)113 232 2480 Healthcare Swansea: +44 (0)1235 239670
Poison Information Centre telephone number	:	Not Available

Date of Compilation/Revision : 24.03.2017 Version : 1.1

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1AH314Serious eye damage, Category 1H318Specific target organ toxicity - single exposure, Category 3,H335

Respiratory system

The classification of this product is based only on its extreme pH value (in accordance with current European legislation).

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms		!
Signal Word	: Danger	
Hazard Statements	: H314 H335	Causes severe skin burns and eye damage. May cause respiratory irritation.
Precautionary Statements	Prevention: P280 Response:	Wear protective gloves/ eye protection/ face protection.
	P303 + P361 + P	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P305 + P351 + P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	P310	present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label: monoethanolamine

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	ClassificationREGULATION (EC) No 1272/2008	Concentration: [%]
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318	>= 5 - < 10
Fattyalcohol ethoxylates > 5EO	69227-22-1	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 5 - < 10

2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6	Eye irritation Category 2; H319	>= 5 - < 1
fatty acids, coco, compds. with ethanolamine	66071-80-5 266-105-0	Serious eye damage Category 2; H319 Skin irritation Category 2; H315	>= 5 - < 1
potassium carbonate	584-08-7 209-529-3 01-2119532646-36	Acute toxicity Category 4; H302 Eye irritation Category 2; H319 Skin corrosion/irritation Category 2; H315 Specific target organ toxicity - single exposure Category 3; H335	>= 3 - < 5
Isotridecanol, ethoxylated	69011-36-5 500-241-6	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 2.5 - <
propan-2-ol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 2.5 - <
alcohols, c13-15-branched and linear, butoxylated ethoxylated	111905-53-4	Skin irritation Category 2; H315 Eye irritation Category 2; H319	>= 2.5 - <
For the full text of the H-S	Statements mentioned	in this Section, see Section 16.	

4.1 Description of first aid measures

In case of eye contact :	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
In case of skin contact :	Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
If swallowed :	Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
If inhaled :	Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

Neomax	l (Neomat/Maxi	I)
--------	----------------	----

circumstances and the surrounding environment.

Unsuitable extinguishing	: None known.
media	

5.2 Special hazards arising from the substance or mixture

Specific haza firefighting	ards during	:	Fire Hazard Keep away from heat and sources of ignition. Flash back possible over considerable distance. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Hazardous c products	ombustion	:	Decomposition products may include the following materials: Carbon oxides nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus
5.3 Advice for fi	refighters		
Special prote for firefighter		:	Use personal protective equipment.

: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel	:	Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Advice for emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

6.2 Environmental precautions

Further information

: Do not allow contact with soil, surface or ground water. Environmental precautions

materials.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	:	Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.
-------------------------	---	--

6.4 Reference to other sections

See Section 1 for emergency contact information. For personal protection see section 8. See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling :	Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling.
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
Storage temperature	:	-5 °C to 40 °C

7.3 Specific end uses

Specific use(s)	: Fl	loor cleaner. Semi-Automatic process
	F	loor cleaner. Manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.		Value type (Form of exposure)	Control parameters	Basis
monoethanolamine	141-43-5		TWA	1 ppm 2.5 mg/m3	UKCOSSTD
Further information				in. The assigned substances are al absorption will lead to system	
			STEL	3 ppm 7.6 mg/m3	UKCOSSTD
Further information				in. The assigned substances are al absorption will lead to systen	
2-(2- butoxyethoxy)ethanol	112-34-5		TWA	10 ppm 67.5 mg/m3	UKCOSSTD
			STEL	15 ppm 101.2 mg/m3	UKCOSSTD
propan-2-ol	67-63-0		TWA	400 ppm 999 mg/m3	UKCOSSTD
			STEL	500 ppm 1,250 mg/m3	UKCOSSTD

DNEL		
2-(2-butoxyethoxy)ethanol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 101.2 mg/m3
		End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 20 mg/kg
		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 67.5 mg/m3
		End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 67.5 mg/m3
propan-2-ol	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 888 mg/cm2
		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m3
		End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 319 mg/cm2
		End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m3
		End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 26 ppm

PNEC

2-(2-butoxyethoxy)ethanol	:	Fresh water Value: 1 mg/l
		Marine water Value: 0.1 mg/l
		Intermittent use/release Value: 3.9 mg/l
		Sewage treatment plant

		Value: 200 mg/l
		Sediment Value: 4 mg/kg
		Soil Value: 0.4 mg/kg
		Oral Value: 56 mg/kg
propan-2-ol	:	Fresh water Value: 140.9 mg/l
		Marine water Value: 140.9 mg/l
		Intermittent use/release Value: 140.9 mg/l
		Fresh water Value: 552 mg/kg
		Marine sediment Value: 552 mg/kg
		Soil Value: 28 mg/kg
		Sewage treatment plant Value: 2251 mg/l
		Oral Value: 160 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Engineering measures	:	Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.
Individual protection measur	es	
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
Eye/face protection (EN 166)	:	Safety goggles Face-shield
Hand protection (EN 374)	:	Recommended preventive skin protection Gloves Nitrile rubber butyl-rubber Breakthrough time: 1 – 4 hours

Neomax I (Neomat/Maxi I)				
	Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.			
Skin and body protection (EN 14605)	: Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing			
Respiratory protection (EN 143, 14387)	: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, 89/686/EEC), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.			

Environmental exposure controls

General advice	: Consider the provision of containment around storage vessels
----------------	--

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	fluorescent, light green
Odour	:	alcohol-like
рН	:	11.9 - 12.9, 100 %
Flash point	:	58 °C closed cup, Does not sustain combustion.
Odour Threshold	:	Not applicable and/or not determined for the mixture
Melting point/freezing point	:	Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	:	Not applicable and/or not determined for the mixture
Evaporation rate	:	Not applicable and/or not determined for the mixture
Flammability (solid, gas)	:	Not applicable and/or not determined for the mixture
Upper explosion limit	:	Not applicable and/or not determined for the mixture
Lower explosion limit	:	Not applicable and/or not determined for the mixture
Vapour pressure	:	Not applicable and/or not determined for the mixture
Relative vapour density	:	Not applicable and/or not determined for the mixture
Relative density	:	1.023 - 1.033
Water solubility	:	soluble
Solubility in other solvents	:	Not applicable and/or not determined for the mixture
Partition coefficient: n- octanol/water	:	Not applicable and/or not determined for the mixture
Auto-ignition temperature	:	Not applicable and/or not determined for the mixture
Thermal decomposition	:	Not applicable and/or not determined for the mixture

Viscosity, kinematic	: 24.363 mm2/s (40 °C)
Explosive properties Oxidizing properties	Not applicable and/or not determined for the mixtureThe substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Decomposition products may include the following materials: Carbon oxides nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure	: Inhalation, Eye contact, Skin contact
Product	
Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: 4 h Acute toxicity estimate : > 5 mg/l
Acute dermal toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Skin corrosion/irritation	: There is no data available for this product.

omov I (Noomot/Movi I)	
omax I (Neomat/Maxi I)	
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.
STOT - single exposure	: There is no data available for this product.
STOT - repeated exposure	: There is no data available for this product.
Aspiration toxicity	: There is no data available for this product.
Components	
Acute oral toxicity	: monoethanolamine LD50 rat: 1,089 mg/kg
	Fattyalcohol ethoxylates > 5EO LD50 : 1,800 mg/kg
	2-(2-butoxyethoxy)ethanol LD50 rat: 3,306 mg/kg
	potassium carbonate LD50 rat: 1,870 mg/kg
	Isotridecanol, ethoxylated LD50 rat: 1,250 mg/kg
	propan-2-ol LD50 rat: 5,840 mg/kg
	alcohols, c13-15-branched and linear, butoxylated ethoxylate LD50 rat: > 2,000 mg/kg
Components	
Acute inhalation toxicity	: monoethanolamine 4 h LC50 rat: 1.6 mg/l
	Fattyalcohol ethoxylates > 5EO LC50 rat: 3.5 mg/l
	potassium carbonate 4 h LC50 rat: 5.26 mg/l
	propan-2-ol 4 h LC50 rat: 30 mg/l
Components	

Components

omax I (Neomat/Max	ki I)
Acute dermal toxicity	: monoethanolamine LD50 rabbit: 1,025 mg/kg
	Fattyalcohol ethoxylates > 5EO LD50 : > 2,000 mg/kg
	2-(2-butoxyethoxy)ethanol LD50 rabbit: 2,764 mg/kg
	potassium carbonate LD50 rabbit: 2,000 mg/kg
	Isotridecanol, ethoxylated LD50 : 2,150 mg/kg
	propan-2-ol LD50 rabbit: 12,870 mg/kg
	alcohols, c13-15-branched and linear, butoxylated ethoxylated LD50 rat: > 2,000 mg/kg
Potential Health Effects	
Eyes	: Causes serious eye damage.
Skin	: Causes severe skin burns.
Ingestion	: Causes digestive tract burns.
Inhalation	: May cause respiratory tract irritation. May cause nose, throat, and lung irritation.
Chronic Exposure	: Health injuries are not known or expected under normal use.
Experience with human	exposure
Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Pain, Corrosion
Ingestion	: Corrosion, Abdominal pain
Inhalation	: Respiratory irritation, Cough

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Environmental Effects	: This product has no known ecotoxicological effects.
Product	
Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae	: no data available
Components	

Neomax I (Neomat/Maxi I)	
Toxicity to fish	: Fattyalcohol ethoxylates > 5EO 96 h LC50: 5 mg/l
	2-(2-butoxyethoxy)ethanol 96 h LC50 Fish: 1,300 mg/l
	potassium carbonate 96 h LC50 Fish: 230 mg/l
	lsotridecanol, ethoxylated LC50: 5.33 mg/l
	propan-2-ol 96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l
	alcohols, c13-15-branched and linear, butoxylated ethoxylated 96 h LC50 Fish: 5 mg/l
Components	
Toxicity to daphnia and other aquatic invertebrates	: monoethanolamine 48 h EC50 Daphnia: 65 mg/l
	propan-2-ol LC50 Daphnia magna (Water flea): > 10,000 mg/l
12.2 Persistence and degradabilit	ty
Product	
Biodegradability	: The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC
Components	
Biodegradability	: monoethanolamine Result: Readily biodegradable.
	Fattyalcohol ethoxylates > 5EO Result: Readily biodegradable.
	2-(2-butoxyethoxy)ethanol Result: Readily biodegradable.
	potassium carbonate Result: Not applicable - inorganic
	Isotridecanol, ethoxylated Result: Readily biodegradable.
	propan-2-ol Result: Readily biodegradable.
	alcohols, c13-15-branched and linear, butoxylated ethoxylated Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste.Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product	Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
Contaminated packaging	Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
Guidance for Waste Code selection	Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number	: 2491
14.2 UN proper shipping	: ETHANOLAMINE, SOLUTION
name	
14.3 Transport hazard	: 8
class(es)	
14.4 Packing group	: 111
14.5 Environmental hazards	: No

14.6 Special precautions for user	: None
Air transport (IATA) 14.1 UN number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special precautions for user	 2491 Ethanolamine solution 8 III No None
Sea transport (IMDG/IMO) 14.1 UN number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special precautions for user 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	 2491 ETHANOLAMINE SOLUTION 8 III No None Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents	: 5 % or over but less than 15 %: Non-ionic surfactants
Regulation EC 648/2004	

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations. The Control of Substances Hazardous to Health Regulations. Health and Safety at Work Act.

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Skin corrosion 1A, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment
Specific target organ toxicity - single exposure	Calculation method

3, H335

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL -Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by

: Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ANNEX: EXPOSURE SCENARIOS

DPD+ Substances:

The following substances are the lead substances that contribute to the mixture Exposure Scenario according to the DPD+ Rule:

Route	Substance	CAS-No.	EINECS-No. 205-483-3	
Ingestion	monoethanolamine	141-43-5		
Inhalation	propan-2-ol	67-63-0	200-661-7	
Dermal	monoethanolamine	141-43-5	205-483-3	
Eyes	monoethanolamine	141-43-5	205-483-3	
aquatic environment	No lead substance			

Physical properties DPD+ Substances:

Substance	Vapour pressure	Water solubility	Pow	Molar Mass
monoethanolamine	0.488 hPa	> 1,000 g/l	0.117	
propan-2-ol	6,020 Pa			60.10 g/mol

To calculate if your downstream Operating Conditions and Risk management Measures are safe, please calculate your risk factor at the website below:

www.ecetoc.org/tra

Short title of Exposure : Scenario	Floor cleaner. Semi-Automatic process
Use descriptors	
Main User Groups :	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Sectors of end-use :	SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories :	PROC10: Roller application or brushing PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Neomax I (Neomat/Maxi I)				
Product categories	:	PC35: Washing and cleaning products (including solvent based products)		
Environmental Release Categories	:	ERC8a: Wide dispersive indoor use of processing aids in open systems		
Short title of Exposure Scenario	:	Floor cleaner. Manual process		
Use descriptors				
Main User Groups	:	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)		
Sectors of end-use	:	SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)		
Process categories	:	PROC10: Roller application or brushing PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities		
Product categories	:	PC35: Washing and cleaning products (including solvent based products)		
Environmental Release : Categories		ERC8a: Wide dispersive indoor use of processing aids in open systems		