

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name	:	MIKRO-QUAT CLASSIC
Product code	:	111187E
Use of the Substance/Mixture	:	Cleaner and disinfectant
Substance type:	:	Mixture
		For professional users only.
Product dilution information	:	0.5 % - 1.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	:	Kitchen cleaner. Manual process Surface disinfectant. Manual process
Recommended restrictions on use	:	Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

F 1 -	Ecolab Ltd. PO Box 11; Winnington Avenue Northwich, Cheshire, United Kingdom CW8 4DX + 44 (0)1606 74488 ccs@ecolab.com
-------------	--

1.4 Emergency telephone number

Emergency telephone	:	+441618841235
number		+32-(0)3-575-5555 Trans-European

Date of Compilation/Revision	:	14.02.2019
Version	:	4.5

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Product AS SOLD	
Skin corrosion, Category 1	H314
Serious eye damage, Category 1	H318
Acute aquatic toxicity, Category 1	H400
Chronic aquatic toxicity, Category 2	H411
The classification of this product is based only o	n its extreme pH value (in accordance with current
European legislation).	

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC Product AS SOLD Hazard pictograms) No 1272/2008)	
Signal Word	: Danger	
Hazard Statements	: H314 H400 H411	Causes severe skin burns and eye damage. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Precautionary Statements	: Prevention: P273 P280 Response:	Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
	P303 + P361 + P3	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P305 + P351 + P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label: benzalkonium chloride

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.3 Other hazards

Product AS SOLD None known. Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Product AS SOLD Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
benzalkonium chloride	68424-85-1 270-325-2 01-2119983287-23	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	>= 5 - < 10

69011-36-5	Acute toxicity Category 4; H302	>= 1 - < 2.5
POLYMER	Serious eye damage Category 1; H318	
7173-51-5	Acute toxicity Category 4; H302	>= 0.5 - < 1
230-525-2	Skin corrosion Category 1B; H314	
01-2119945987-15	Chronic aquatic toxicity Category 2; H411	
	Acute aquatic toxicity Category 1; H400	
lace exposure limit :		
107-21-1	Acute toxicity Category 4; H302	>= 0.25 - < 0.5
203-473-3		
01-2119456816-28	exposure Category 2; H373	
	POLYMER 7173-51-5 230-525-2 01-2119945987-15 lace exposure limit : 107-21-1	POLYMERSerious eye damage Category 1; H3187173-51-5 230-525-2 01-2119945987-15Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Chronic aquatic toxicity Category 2; H411 Acute aquatic toxicity Category 1; H400Iace exposure limit : 107-21-1 203-473-3Acute toxicity Category 4; H302 Specific target organ toxicity - repeated

Product AT USE DILUTION Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
benzalkonium chloride	68424-85-1 270-325-2 01-2119983287-23	Acute toxicityCategory 4; H302 Skin corrosionCategory 1B; H314 Serious eye damageCategory 1; H318 Acute aquatic toxicityCategory 1; H400 Chronic aquatic toxicityCategory 1; H410	< 0.1

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

Product AS SOLD In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
In case of skin contact	: Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
If swallowed	: Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If conscious, give 2 glasses of water. Get medical attention immediately.
If inhaled	: Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
Product AT USE DILUTION	
In case of eye contact	: Rinse with plenty of water.
In case of skin contact	: Rinse with plenty of water.
If swallowed	: Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment

: Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

for firefighters

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	: Not flammable or combustible.
Hazardous combustion products	 Depending on combustion properties, decomposition products may include following materials: Carbon oxides nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus
5.3 Advice for firefighters	
Special protective equipment	: Use personal protective equipment.

explosion do not breathe fumes.	Further information		Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.
---------------------------------	---------------------	--	--

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD Advice for non-emergency personnel	: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Advice for emergency : responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency	:	Refer to protective measures listed in sections 7 and 8.
personnel		
Advice for emergency		If specialised clothing is required to deal with the spillage, take
0 ,	•	
responders		note of any information in Section 8 on suitable and unsuitable
		materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions	:	Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION	
Environmental precautions :	No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up	:	Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.
Product AT USE DILUTION		
Methods for cleaning up	:	Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information. For personal protection see section 8. See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD Advice on safe handling	: Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
Product AT USE DILUTION Advice on safe handling	: Wash hands after handling. For personal protection see section 8.
	- · · ·
Hygiene measures	: Wash hands before breaks and immediately after handling the

		product.			
7.2 Cond	7.2 Conditions for safe storage, including any incompatibilities				
Requareas	luct AS SOLD uirements for storage s and containers age temperature	 Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers. -5 °C to 40 °C 			
Requ	luct AT USE DILUTION uirements for storage s and containers	: Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.			
7.3 Spec	ific end uses				
	luct AS SOLD sific use(s)	: Kitchen cleaner. Manual process Surface disinfectant. Manual process			

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Product AS SOLD

Occupational Exposure Limits

Components	CAS-No.		Value type (Form of exposure)	Control parameters	Basis
Ethylene Glycol	107-21	-1	TWA (Vapour.)	20 ppm 52 mg/m3	UKCOSSTD
Further information	Sk			in. The assigned substances are al absorption will lead to system	
			STEL (Vapour.)	40 ppm 104 mg/m3	UKCOSSTD
Further information	Sk			in. The assigned substances are al absorption will lead to system	
			TWA (particles)	10 mg/m3	UKCOSSTD
Further information	Sk			in. The assigned substances are al absorption will lead to system	

DNEL

:	End Use: Workers
	Exposure routes: Skin contact
	Potential health effects: Long-term systemic effects
	Value: 106 mg/cm2
	End Use: Workers
	Exposure routes: Inhalation
	Potential health effects: Long-term systemic effects
	Value: 35 mg/m3
	C C
	End Use: Consumers
	Exposure routes: Skin contact
	Potential health effects: Long-term systemic effects
	Value: 53 mg/cm2
	5
	End Use: Consumers
	Exposure routes: Inhalation
	:

MIKRO-QUAT CLASSIC Potential health effects: Long-term systemic effects Value: 7 mg/m3

PNEC

PNEC		
Ethylene Glycol	: Fresh water	
	Value: 10 mg/l	
	Marine water	
	Value: 1 mg/l	
	Water	
	Value: 10 mg/l	
	Fresh water sediment	
	Value: 20.9 mg/kg	
	Water	
	Value: 1995.5 mg/l	
	Soil	
	Value: 1.53 mg/kg	

8.2 Exposure controls

Product AS SOLD Appropriate engineering controls

Engineering measures	:	Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.
Individual protection measure	es	
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
Eye/face protection (EN 166)	:	Safety goggles Face-shield
Hand protection (EN 374)	:	Recommended preventive skin protection Gloves Nitrile rubber butyl-rubber Breakthrough time: 1 – 4 hours Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin and body protection (EN 14605)	:	Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387)	:	None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.
Product AT USE DILUTION Appropriate engineering cor	ntre	bls
Engineering measures		Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measured	res	;
Hygiene measures	:	Wash hands before breaks and immediately after handling the product.
Eye/face protection (EN 166)	:	No special protective equipment required.
Hand protection (EN 374)	:	No special protective equipment required.
Skin and body protection (EN 14605)	:	No special protective equipment required.
Respiratory protection (EN 143, 14387)	:	None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.
Environmental exposure cor	atr.	

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

	Product AS SOLD	Product AT USE DILUTION		
Appearance	: liquid	liquid		
Colour	: clear, purple			
Odour	: Perfumes, fragrances	very faint		
рН	: 11.9 - 12.9, 100 %	9.5 - 9.6		
Flash point	: Not applicable.	Not applicable.		
Odour Threshold	: Not applicable and/or not deter	Not applicable and/or not determined for the mixture		
Melting point/freezing point	: Not applicable and/or not deter	Not applicable and/or not determined for the mixture		
Initial boiling point and	Not applicable and/or not determined for the mixture			

boiling range	
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.046 - 1.056
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n- octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Acids

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials: Carbon oxides nitrogen oxides (NOx) Sulphur oxides

Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

Product AS SOLD Information on likely routes of exposure	:	Inhalation, Eye contact, Skin contact
Product		
Acute oral toxicity	:	Acute toxicity estimate : > 2,000 mg/kg
		Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	:	There is no data available for this product.
Acute dermal toxicity	:	There is no data available for this product.
Skin corrosion/irritation	:	There is no data available for this product.
Serious eye damage/eye irritation	:	There is no data available for this product.
Respiratory or skin sensitization	:	There is no data available for this product.
Carcinogenicity	:	There is no data available for this product.
Reproductive effects	:	There is no data available for this product.
Germ cell mutagenicity	:	There is no data available for this product.
Teratogenicity	:	There is no data available for this product.
STOT - single exposure	:	There is no data available for this product.
STOT - repeated exposure	:	There is no data available for this product.
Aspiration toxicity	:	There is no data available for this product.
Components		
Acute oral toxicity	:	benzalkonium chloride LD50 rat: 344 mg/kg
		Alcohols, C13, branched, ethoxylated LD50 rat: > 500 mg/kg
		Didecyl Dimethyl Ammonium Chloride LD50 rat: 1,150 mg/kg
Components		
Acute dermal toxicity	:	benzalkonium chloride LD50 rabbit: 3,340 mg/kg

Didecyl Dimethyl Ammonium Chloride LD50 rabbit: 2,930 mg/kg

Ethylene Glycol LD50 rabbit: 10,600 mg/kg

Potential Health Effects

Product AS SOLD Eyes	: Causes serious eye damage.
Skin	: Causes severe skin burns.
Ingestion	: Causes digestive tract burns.
Inhalation	: May cause nose, throat, and lung irritation.
Chronic Exposure	: Health injuries are not known or expected under normal use.
Product AT USE DILUTION Eyes	: Health injuries are not known or expected under normal use.
Skin	: Health injuries are not known or expected under normal use.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.
Chronic Exposure	: Health injuries are not known or expected under normal use.
Experience with human expo	sure
Product AS SOLD Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Pain, Corrosion
Ingestion	: Corrosion, Abdominal pain
Inhalation	: Respiratory irritation, Cough
Product AT USE DILUTION Eye contact	: No symptoms known or expected.
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD 12.1 Ecotoxicity

Environmental Effects	:	Very toxic to aquatic life. Toxic to aquatic life with long lasting
		effects.

Product		
Toxicity to fish	:	no data available
Toxicity to daphnia and other aquatic invertebrates	:	no data available
Toxicity to algae	:	no data available
Components		
Toxicity to fish	:	Alcohols, C13, branched, ethoxylated 96 h LC50 Fish: 3 mg/l
		Didecyl Dimethyl Ammonium Chloride 96 h LC50 Fish: 1 mg/l
		Ethylene Glycol 96 h LC50: 72,860 mg/l
Components		
Toxicity to daphnia and other aquatic invertebrates	:	benzalkonium chloride 48 h EC50 Daphnia magna (Water flea): 0.016 mg/l
		Alcohols, C13, branched, ethoxylated 48 h EC50 Daphnia magna (Water flea): 1.5 mg/l
		Ethylene Glycol 48 h EC50: > 100 mg/l
Components		
Toxicity to algae	:	Ethylene Glycol 96 h EC50: 6,500 mg/l
12.2 Persistence and degradabil	ity	
Product		
Biodegradability	:	The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC
Components		
Biodegradability	:	benzalkonium chloride Result: Biodegradable
		Alcohols, C13, branched, ethoxylated Result: Biodegradable
		Didecyl Dimethyl Ammonium Chloride Result: Eliminated from aquatic environment
		Ethylene Glycol Result: Readily biodegradable.
12.3 Bioaccumulative potential		

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste.Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD Product	:	The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
Contaminated packaging	:	Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
Guidance for Waste Code selection	:	Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.
Product AT USE DILUTION Product	:	Diluted product can be flushed to sanitary sewer.
Contaminated packaging	:	Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport	(ADR/ADN/RID)
----------------	---------------

14.1 UN number 14.2 UN proper shipping name	: 1760 : CORROSIVE LIQUID, N.O.S.
14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards	(quaternary ammonium compound) : 8 : III : Yes
14.6 Special precautions for user	: None
Air transport (IATA) 14.1 UN number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group	 1760 Corrosive liquid, n.o.s. (quaternary ammonium compound) 8 III
14.5 Environmental hazards 14.6 Special precautions for user	: Yes : None
Sea transport (IMDG/IMO) 14.1 UN number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards	 1760 CORROSIVE LIQUID, N.O.S. (quaternary ammonium compound) 8 III Yes
14.6 Special precautions for user 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	: None : Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents : Regulation EC 648/2004	5 % or over but less than 15 %: Cationic surfactants less than 5 %: Non-ionic surfactants Other constituents: Perfumes Preservation agents: Didecyl Dimethyl Ammonium Chloride Contains: Disinfectants Allergens: Limonen Citral
---	--

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations	: The Chemicals (Hazard Information and Packaging for Supply) Regulations.
	The Control of Substances Hazardous to Health Regulations. Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification				
Skin corrosion 1, H314	On basis of test data.				
Serious eye damage 1, H318	Based on product data or assessment				
Acute aquatic toxicity 1, H400	Calculation method				
Chronic aquatic toxicity 2, H411	Calculation method				

Full text of H-Statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL -Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS

 Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Further information

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Kitchen cleaner. Manual process

Life Cycle Stage	:	Widespread use by professional workers		
Product category	:	PC35	Washing and cleaning products (including solvent based products)	

Contributing scenario controlling environmental exposure for:

Environmental release category	:	ERC8a	Wide dispersive indoor use of processing aids in open systems
Daily amount per site	:	7.5 kg	
Type of Sewage Treatment Plant	:	Municipal s	ewage treatment plant

Contributing scenario controlling worker exposure for:

Process category	:	PROC10	Roller application or brushing
Exposure duration	:	480 min	
Operational conditions and risk management measures	:	Indoor	

General ventilation Ventilation rate per hour 1 Skin Protection : No Respiratory Protection : No Contributing scenario control : No Process category : PROCBa Transfer of substance or preparation (charging) General ventilation : 60 min Operational conditions and : indoor Operational conditions and : : Indoor indoor indoor Skin Protection : indoor indoor indoor Skin Protection : Yes: See Section 8 indoor indoor Respiratory Protection : No indoor indoor indoor Skin Protection : Yes: See Section 8 indoor indoor indoor Exposure Scenario: Surface : Ves: See Section 8 indoor indoor indoor Exposure Scenario: Surface : PC35 Washing and cleaning products (including solvent based products) indoor Environmental release : : RCF3 Wide dispersive indoor use of processing aids in open systems indoor <th></th> <th></th> <th>Local Exha</th> <th colspan="3">Local Exhaust Ventilation is not required</th>			Local Exha	Local Exhaust Ventilation is not required		
Respiratory Protection : No Contributing scenario contrectors worker exposure for: Process category : PROC8a Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non- dedicated facilities Exposure duration : 60 min Image: Contributing scenario contrections Operational conditions and risk management measures : Indoor Image: Contributing scenario contrections General ventilation : Indoor : Image: Contributing scenario contrections 1 Skin Protection : Ventilation rate per hour 1 1 Skin Protection : No : Stepsure Scenario: Surface textext. Manual process Life Cycle Stage : : Widespread use by professional workers : Product category : : Wide dispersive indoor use of processing aids in open systems Daily amount per site : : : : Process category : : Municipal sewage treatment plant : Process category : : : : : Dip of Sewage Treatment Plant	General ventilation		Ventilation	rate per hour 1		
Contributing scenario controller worker exposure for: Process category i PROC8a Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non- decicated facilities Exposure duration i 60 min Operational conditions and risk management measures i Indoor Exposure duration i Indoor Exposure duration i Indoor Skin Protection i Ventilation rate per hour 1 Skin Protection : Ventilation rate per hour 1 Skin Protection : Ventilation store secons - Respiratory Protection : No - Exposure Scenario: Surface : Widespread use by professional workers - Product category : PC35 Washing and cleaning products (including solvent based products) - Contributing scenario control : : : - - Product category : PC35 Wide dispersive indoor use of processing aids in open systems - Daily amount per site : : : : - Process ca	Skin Protection	:	No			
Process category : PROC8a Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities Exposure duration : : 0 or nin Operational conditions and risk management measures : Indoor Exposure duration : : Local Exhaust Ventilation is not required General ventilation : Ventilation rate per hour 1 Skin Protection : No . Exposure Scenario: Surface discretation to transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities 1 Exposure Scenario: Surface discretation : No . Exposure Scenario: Surface discretation : No . Exposure Scenario: Surface discretation : No . Exposure Scenario controlectation : Widespread use by professional workers . Product category : : PC35 Washing and cleaning products (including solvent based products) Daily amount per site : 7.5 kg . . Type of Sewage Treatment Plant : Municipal sewage treatment plant <t< td=""><td>Respiratory Protection</td><td>:</td><td>No</td><td></td></t<>	Respiratory Protection	:	No			
Process category : PROC8a Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities Exposure duration : : 0 or nin Operational conditions and risk management measures : Indoor Exposure duration : : Local Exhaust Ventilation is not required General ventilation : Ventilation rate per hour 1 Skin Protection : No . Exposure Scenario: Surface discretation to transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities 1 Exposure Scenario: Surface discretation : No . Exposure Scenario: Surface discretation : No . Exposure Scenario: Surface discretation : No . Exposure Scenario controlectation : Widespread use by professional workers . Product category : : PC35 Washing and cleaning products (including solvent based products) Daily amount per site : 7.5 kg . . Type of Sewage Treatment Plant : Municipal sewage treatment plant <t< td=""><td>Contributing sconario contr</td><td></td><td>ng worker e</td><td>vnosure for:</td></t<>	Contributing sconario contr		ng worker e	vnosure for:		
discharging) from/ to vessels/ large containers at non- dedicated facilities Exposure duration : 60 min Operational conditions and risk management measures : Indoor Exposure duration : Local Exhaust Ventilation is not required General ventilation : Local Exhaust Ventilation is not required General ventilation : Yes: See Section 8 Respiratory Protection : No Exposure Scenario: Surface distrectant. Manual process Indoor Life Cycle Stage : Widespread use by professional workers Product category : PC35 Washing and cleaning products (including solvent based products) Contributing scenario controlition reviewer to systems systems Indoor Daily amount per site : 7.5 kg Type of Sewage Treatment : Municipal sewage treatment plant Process category : PROC10 Roller application or brushing Exposure duration : 480 min Indoor Operational conditions and risk management measures : Indoor Exposure duration : Indoor Indoor	-	Unin	•			
Operational conditions and risk management measuresindoorLocal Exhaust Ventilation is not required	Process category	÷	PROC8a	discharging) from/ to vessels/ large containers at non-		
rišk management measures Local Exhaust Ventilation is not required General ventilation Ventilation rate per hour N Ventilation rate per hour Ventilation rate per hour Ventilation rate per hour Ventilation Venti	Exposure duration	:	60 min			
General ventilation Ventilation rate per hour 1 Skin Protection : Yes: See Section 8 Respiratory Protection : No Exposure Scenario: Surfactority Fectant: Manual process Life Cycle Stage : Widespread use by professional workers Product category : PC35 Washing and cleaning products (including solvent based products) Contributing scenario contributing scenario contributing scenario : ERC8a Wide dispersive indoor use of processing aids in open systems Daily amount per site : ICC8a Workie auge treatment plant : Process category : PROC10 Roller application or brushing : Exposure duration : 480 min : : . Operational conditions and risk management measures : Indoor : : Kin Protection : Ventilation rate per hour 1 : Skin Protection : No : :	•	:	Indoor			
Skin Protection : Yes: See Section 8 Respiratory Protection : No Exposure Scenario: Surface disinfectant. Manual process Life Cycle Stage : Widespread use by professional workers Product category : PC35 Washing and cleaning products (including solvent based products) Contributing scenario controlling environmental exposure for: Environmental release : ERC8a Wide dispersive indoor use of processing aids in open systems Daily amount per site : 7.5 kg Type of Sewage Treatment : Municipal sewage treatment plant : Process category : PROC10 Roller application or brushing : : Exposure duration : 480 min : . : : Operational conditions and risk management measures : Indoor : <			Local Exha	ust Ventilation is not required		
Respiratory Protection : No Exposure Scenario: Surface stretcant. Waves Secondaria stretcant. Waves Life Cycle Stage : Widespread use by professional workers Product category : PC35 Washing and cleaning products (including solvent based products) Contributing scenario controtrotrotrotrotrotrotrotrotrotrotrotrot	General ventilation		Ventilation	rate per hour 1		
Exposure Scenario: Surface is:infectant. Manual process Life Cycle Stage : Widespread use by professional workers Product category : PC35 Washing and cleaning products (including solvent based products) Contributing scenario contrest environmental release category : ERC8a Wide dispersive indoor use of processing aids in open systems Daily amount per site : 7.5 kg Municipal sewage treatment plant Plant	Skin Protection	:	Yes: See S	Section 8		
Life Cycle Stage:Widespread use by professional workersProduct category:PC35Washing and cleaning products (including solvent based products)Contributing scenario controllerent environmental exposure for:Environmental release:ERC8aWide dispersive indoor use of processing aids in open systemsDaily amount per site:7.5 kg	Respiratory Protection	:	No			
Life Cycle Stage:Widespread use by professional workersProduct category:PC35Washing and cleaning products (including solvent based products)Contributing scenario controllerent environmental exposure for:Environmental release:ERC8aWide dispersive indoor use of processing aids in open systemsDaily amount per site:7.5 kg	Exposure Scenario: Surface	a die	sinfectant N	lanual process		
Product category:PC35Washing and cleaning products (including solvent based products)Contributing scenario controller environmental exposure for:Environmental release category:ERC8aWide dispersive indoor use of processing aids in open systemsDaily amount per site:7.5 kgType of Sewage Treatment Plant:Municipal sewage treatment plantPlant:Municipal sewage treatment plantProcess category:PROC10Roller application or brushing:Exposure duration:0perational conditions and risk management measures:Contributing scenario:0perational conditions and risk management measures:Skin Protection:No:	-					
Contributing scenario controlling environmental exposure for: Environmental release category : ERC8a Wide dispersive indoor use of processing aids in open systems Daily amount per site : 7.5 kg Type of Sewage Treatment : Municipal sewage treatment plant Plant : Municipal sewage treatment plant Process category : PROC10 Roller application or brushing Exposure duration : 480 min Operational conditions and risk management measures : Indoor Skin Protection : No	Life Cycle Stage	:				
Environmental release category:ERC8aWide dispersive indoor use of processing aids in open systemsDaily amount per site:7.5 kgType of Sewage Treatment Plant:Municipal sewage treatment plantContributing scenario controllor worker exposure for:Process category:PROC10Roller application or brushing:Exposure duration:480 minOperational conditions and risk management measures:Indoor:Local Exhaust Ventilation is not requiredGeneral ventilation:No	Product category	:	PC35			
Environmental release category:ERC8aWide dispersive indoor use of processing aids in open systemsDaily amount per site:7.5 kgType of Sewage Treatment Plant:Municipal sewage treatment plantContributing scenario controllor worker exposure for:Process category:PROC10Roller application or brushing:Exposure duration:480 minOperational conditions and risk management measures:Indoor:Local Exhaust Ventilation is not requiredGeneral ventilation:No			_			
categorysystemsoDaily amount per site:7.5 kgType of Sewage Treatment:Municipal sewage treatment plantPlant:Municipal sewage treatment plantProcess category:PROC10Roller application or brushingExposure duration:0perational conditions and risk management measures:Indoor.Local Exhaust Ventilation is not requiredGeneral ventilationVentilation rate per hour1	Contributing scenario controlling environmental exposure for:					
Type of Sewage Treatment : Municipal sewage treatment plant Plant : Municipal sewage treatment plant Contributing scenario controlling worker exposure for: : Process category : PROC10 Exposure duration : 480 min Operational conditions and risk management measures : Indoor Local Exhaust Ventilation is not required : 1 Skin Protection : No		:	ERC8a			
Plant Contributing scenario controlling worker exposure for: Process category : PROC10 Roller application or brushing Exposure duration : 480 min Operational conditions and risk management measures : Indoor Local Exhaust Ventilation is not required Local Exhaust Ventilation is not required Skin Protection : No	Daily amount per site	:	7.5 kg			
Process category: PROC10 Roller application or brushingExposure duration:480 minOperational conditions and risk management measures:IndoorLocal Exhaust Ventilation is not requiredGeneral ventilation:Ventilation rate per hourSkin Protection:No		:	Municipal s	ewage treatment plant		
Exposure duration:480 minOperational conditions and risk management measures:IndoorLocal Exhaust Ventilation is not requiredLocal Exhaust Ventilation is not requiredGeneral ventilationVentilation rate per hour1Skin Protection:No	Contributing scenario controlling worker exposure for:					
Operational conditions and risk management measures:IndoorLocal Exhaust Ventilation is not requiredLocal Exhaust Ventilation is not requiredGeneral ventilationVentilation rate per hour1Skin Protection:No	Process category	:	PROC10	Roller application or brushing		
risk management measures Local Exhaust Ventilation is not required General ventilation Ventilation rate per hour 1 Skin Protection : No	Exposure duration	:	480 min			
General ventilation Ventilation rate per hour 1 Skin Protection : No		:	Indoor			
Skin Protection : No			Local Exha	ust Ventilation is not required		
	General ventilation		Ventilation	rate per hour 1		
111187E 17 / 18	Skin Protection	:	No			
	111187E			17 / 18		

Respiratory Protection : No

Contributing scenario controlling worker exposure for:

Process category	:	PROC8a	Transfer of substance or preparation (chargi discharging) from/ to vessels/ large containe dedicated facilities	
Exposure duration	:	60 min		
Operational conditions and risk management measures	:	Indoor		
		Local Exhau	ust Ventilation is not required	
General ventilation		Ventilation r	ate per hour	1
Skin Protection	:	Yes: See Se	ection 8	
Respiratory Protection	:	No		